

SpotOn®

Floor 200

SpotOn® Floor 200 is a print media for short-term, indoor floor graphics without the need for lamination. It boasts a post-printed "low slip potential" rating according to the EN 13036-4 Pendulum Test which is endorsed by the CTIOA, that allows for vibrant, slip-resistant floor graphics. SpotOn® Floor 200 has been specifically developed for a simple, easy and tool-free installation. Thanks to a unique dot-pattern printed pressure-sensitive polyacrylate adhesive, this film can be applied to multiple flooring surfaces including floor or ceramic tiles, sealed wood, concrete, waxed vinyl, marble, terrazzo surfaces and more. It can also be cleanly and quickly removed within six months of application.

- IDEAL FOR SHORT TERM INDOOR FLOOR APPLICATIONS
- EASY TOOL FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 6 MONTHS

8 mil White Monomeric PVC

Matte

 (Eco) Solvent Latex UV

 DOT Pattern Removable Adhesive

 Widths up to 54 in

 MONTHS DURABILITY **6** INTERIOR

SLIP-CERTIFIED WITHOUT LAMINATION



APPLICATIONS

APPLIED TO FLOOR,
CERAMIC TILES,
SEALED WOOD,
CONCRETE, WAXED VINYL,
MARBLE OR TERRAZZO.



Certified for
HP Latex Inks

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Floor 200

SpotOn® Floor 200 is a 200µ (8 mil) embossed printable white matte monomeric PVC film, coated on one side with a dot-pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single sided, siliconized clay coated kraft release liner. This high quality ink receptive embossed white vinyl was specifically developed for easy application. SpotOn® Floor 200 has a post-printed "low slip potential" rating according to the EN 13036-4 Pendulum Test which is endorsed by the CTIOA, that allows for vibrant, slip resistant floor graphics without the need for lamination.

- IDEAL FOR SHORT TERM INDOOR FLOOR GRAPHIC PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 6 MONTHS

INSTALLATION RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	White Matte Monomeric PVC
Adhesive	Dot-Pattern Removable Polyacrylate
Release Liner	135 gsm Siliconized 1 Side Bleached Clay Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	8 mil (200µ)	8.8 mil
Adhesive Layer	0.6 mil (15µ)	(215µ)
Film/Adhesive Ratio	8.0:0.6	
UV Protection Factor	Not Applicable	
Outdoor Durability	Internal Use Only	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Slip Rating	Low Slip Potential - Post-Printed (EN 13036-4 Pendulum Test)	
Shelf Life	2 years	
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

PRINTING RECOMMENDATIONS
UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013